

Specification 2500HBFP 30min

TECHNICAL INFORMATION

2820mm
1500mm
1650mm
2500 litres
300 kilograms
Medium density polyethylene
Yes
2" BSP
30 minute

PRODUCT DESCRIPTION

2500 litres bunded, fire protected tank.

SPECIFICATION

- 2" BSP fill connection c/w cap and chain
- **◊** Vent
- Watchman contents gauge
- Gas strut assisted flip lid for ease when opening the lid of the tank
- 1" bottom outlet (10mm top outlet available upon request)
- Overfill prevention valve
- Clock gauge
- ٥ 30 minute fire retardant material

OPTIONAL EXTRAS

- Fire protection Tuffa UK has pioneered the fire protected oil tank, and ٥ developed a patented high quality fire retardant material mounted between the primary tank and outer layer of the tank. This material has been tested and certified to BS476 to give at least 30 and 60 minutes protection by Warrington Fire Research Centre (now Bodycote Global) and is suitable for both domestic and commercial applications.
- Fittings Pack (1" 1/2" adaptor, ball valve and filter)

Manufacturers of liquid storage tanks up to 100,000 litres.

Easi-fill Bunded Range

Easi-fill Fuel Stations

Interlinked Tanks

Dual & Triple storage compartment tanks

Biodiesel Storage

Tank Fire Protection

Waste Oil tanks, **Bowsers & Chemical** Tanks

Petrol Storage

Rain Water Harvesting

AdBlue Systems

T: 08707 567700 F: 01889 567600

www.tuffa.co.uk sales@tuffa.co.uk

Registered office address:

TUFFA UK Limited Dovefields Industrial Estate Derby Road Uttoxeter Staffordshire ST14 8SW





Your in-house Liquid Storage Solution Partners

0.5.0.8

LABC



Tuffa® is a registered trademark of TUFFA UK Limited